




Doppelwandiges Drainage-Wellrohr.

In 50m bzw. 25m Rollen mit Einziehband aus Nylon.



von DN63 - DN125 mm



von DN140 - DN200 mm



Ø außen DN/OD (mm)	63	75	90	110	125	140	160	200
Ø innen (mm)	50	60	73	92	105	120	137	171
Wandstärke am Perforationspunkt (mm)	1,3	1,4	1,5	1,5	1,5	1,5	1,5	1,5
Wellenzahl pro Laufmeter	140	111	111	99	99	80	66	50
Anzahl Schlitze pro Rille	3	3	3	3	3	6	6	6
Schlitze pro Laufmeter	210	167	167	149	149	240	198	150
Winkel zwischen angrenzenden Schlitzen	60°	60°	60°	60°	60°	60°	60°	60°
Drainagefläche (cm ² /ml)	>65	>65	>75	>80	>85	>90	>110	>125
Druckfestigkeit (N/lfm)	300	300	300	300	300	300	300	300
Rollenlänge (lfm)	50	50	50	50	50	50	50	25
Außenwandmaterial	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE
Innenwandmaterial	LDPE	LDPE	LDPE	LDPE	LDPE	LDPE	LDPE	LDPE