



Nenn-durch-messer (mm)	Nenn-durch-messer (Zoll)	Aussendurch-messer (mm)
300	12"	324,3
350	14"	376,1
400	16"	427,1
450	18"	475,3
500	20"	530,1
600	24"	633,1
700	28"	718,3
800	32"	819,9
900	36"	924,1
1000	40"	1026,1
1100	44"	1125,0
1200	48"	1228,8
1300	52"	1331,5
1400	56"	1433,6
1500	60"	1535,6
1600	64"	1637,6
1700	68"	1739,4

Nenn-durch-messer (mm)	Nenn-durch-messer (Zoll)	Aussendurch-messer (mm)
1800	72"	1841,7
1900	76"	1943,4
2000	80"	2045,8
2100	84"	2147,9
2200	88"	2250,0
2300	92"	2351,4
2400	96"	2453,0
2500	100"	2555,0
2600	104"	2657,0
2700	108"	2758,0
2800	112"	2860,0
2900	116"	2962,0
3000	120"	3065,0
3100	124"	3167,0
3200	128"	3269,0
3300	132"	3371,0
3400	136"	3473,0

Winkelabweichungen bei SUPERLIT-Kupplungen

DN (mm)	Winkelabweichung (Grad)
DN ≤ 500	3.0
500 < DN ≤ 900	2.0
900 < DN ≤ 1800	1.0
1800 < DN	0.5

